

DS-2CD2014WD-I

1.0MP WDR IR Bullet Network Camera



Key features

- HD720p video
- 100dB WDR
- 3D DNR
- Up to 30m IR
- IP66

Dimensions



Available models

DS-2CD2014WD-I

DS-2CD2014WD-I	
Camera	
Image sensor	1/4" Progressive Scan CMOS
Min. illumination	0.01 lux @F1.2, AGC ON, 0 lux with IR
Shutter Speed	1/25s to 1/100,000s
Lens	4mm @ F2.0, Angle of view: 55° (8mm, 12mm optional)
Lens mount	M12
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	100dB
Compression Standard	
Video compression	H.264 / MJPEG
Video Bit Rate	32 Kbps - 16 Mbps
Dual Stream	Yes
Image	
Max. Image Resolution	1280 × 960
Frame rate	50 Hz: 25 fps (1280 × 720), 25 fps (704 × 576), 25 fps (640 × 480) 60 Hz: 30 fps (1280 × 720), 30 fps (704 × 576), 30 fps (640 × 480)
Image settings	Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser
BLC	Yes, zone configurable
ROI	Yes, up to 4 configurable areas
Network	
Network storage	NAS
Alarm trigger	Motion detection, Dynamic analysis, Tampering alarm
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, P2P, Bonjour
Security	User Authentication, Watermark
Standard	ONVIF, PSIA, CGI, ISAPI
Interface	
Communication Interface	1 RJ45 10M/100M Ethernet interface
Reset Button	Yes
General	
Operating conditions	-30 °C - 60 °C (-22 °F - 140 °F), Humidity 95% or less (non-condensing)
Power supply	12 VDC ± 10% , PoE (802.3af)
Power consumption	Max. 6 W
Weather proof rating	IP66
IR range	30 meters
Dimension	80.4×76.3×139.28 mm (2.4" × 3.0" × 5.5")
Weight	500g (1.1 lbs)